

CHAPTER 4

ONE-WAY, THROUGH, YIELD STREETS

SECTION:

- 9-4-1: One-Way Streets and Alleys
- 9-4-2: Through Streets
- 9-4-3: Yield Streets
- 9-4-4: Signs at Through Streets and Yield Streets
- 9-4-5: Stop and Yield Signs

9-4-1: ONE-WAY STREETS AND ALLEYS:

A. Signs Required. When any one-way street is designated, the Street Commissioner shall place and maintain signs giving notice thereof, and no such regulations shall be effective unless such signs are in place. Signs indicating the direction of lawful traffic movement shall be placed at every intersection where movement of traffic in the opposite direction is prohibited.

B. Designation. Upon those streets and parts of streets and in those alleys described in Schedule I of Chapter 10, vehicular traffic shall move only in the indicated direction of traffic are erected and maintained at every intersection where movement in the opposite direction is prohibited. (1963 Code, * 36.23)

9-4-2: THROUGH STREETS: Those streets and parts of streets described in Schedule II and Schedule IV of Chapter 10 are hereby declared to be through streets or stop streets for the purpose of this Chapter. (1963 Code, * 36.24)

9-4-3: YIELD STREETS: Those streets and parts of streets described in Schedule III of Chapter 10 are hereby declared to be yield streets for the purpose of this Chapter. (1963 Code, * 36.25)

9-4-4: SIGNS AT THROUGH STREETS AND YIELD STREETS: Whenever this Chapter designates and describes a through street or yield street it shall be the duty of the Street Commissioner to place and maintain a stop sign, or a yield sign, on every street intersecting such through street or yield street, unless traffic at any such intersection is controlled by traffic control signs, provided however, that at the intersection of two (2) such through streets or at the intersection of a through street and heavy traffic street not so designated, stop signs shall be erected at the approach of either of said streets as may be determined by the Street Commissioner upon the basis of an engineering and traffic study. (1963 Code, *36.26)

9-4-5: STOP AND YIELD SIGNS:

A. Every stop sign shall bear the word "Stop" in letters not less than eight inches (8") in height. Every yield sign shall bear the word "Yield" in letters not less than seven inches (7") in height.

Every stop sign and yield sign shall at nighttime be rendered luminous by internal illumination, or by a floodlight projected on the face of the sign, or by efficient reflecting elements in the face of the sign.

B. Every stop sign and every yield sign shall be erected as near as practicable to the nearest line of the crosswalk on the near side of the intersection or, if there is no crosswalk, then as near as practicable to the nearest line of the intersecting roadway. (1963 Code, * 36.27)